Logo Placements

6763 ProtecWork Women's Stretch Trousers

Recommended logo placements


Heat seal & Embroidery

11	Rear side of left leg (calf), centered between the seams, start 5 above lowest point of leg.
16	Rear side of right leg (calf), centered between the seams, start 5 above lowest point of leg.
28	Rear side of right leg, 1 cm from side seam, start 5 above lowest point of leg.
34	Rear side of left leg, 1 cm from side seam, start 5 above lowest point of leg.
100	Right leg, 2 cm above knee pocket seam, maximum size 100x100 mm
101	Left leg, centered 2 cm above knee pocket seam, maximum size 100x100 mm

Heat seal

18	Centered, 2 cm below pocket seam, maximum sizwe 100x60 mm
20	Left leg pocket, centered, maximum size 100x40 mm
29	Right leg-pocket flap, maximum size 100x30 mm
30	Left leg-pocket flap, maximum size 100x30 mm

Placement 11, 16, 28 and 34, maximum size for embroidery 80x250 mm and for heat seal 160x250 mm



Add:
B after the placement and it will be below the (1B)
Y and it will be turned from bottom to top
Z after the placement and it will be turned from top to bottom





How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm^2 shall be tested in ISO 15025, Procedure A.



Right side of trouser



Left side of trouser

https://www.snickersworkwear.com/contact